ORIGINAL

PELLET STATIC ELIMINATOR

Eliminator MSE For resin pellets only



A POWERFUL STATIC ELIMINATOR DEDICATED TO RESIN PELLETS

Stabilization of molding conditions to prevent re-absorption



SUMMARY

STATIC ELIMINATOR

Proven technology from a long experienced manufacturer with high performance. Available to adjust the electric potential to positive or negative. Prevent powering and floss cross sections are minimized. Long life span of approximately 8 years.





- Stabilization of molding conditions
- Prevent Re-absorption
- Accelerate recycling material's flow
- Prevent white spots and black spots
- Prevent color unevenness
- Prevent recycled material separation
- No material accumulation
- Reduce the metal detector's malfunction
- Less maintenance, Less powder.
- Ensure the glass-tube visibly.

30.00%				
25.00%				
20.00%				
15.00%				
10.00%				
5.00%				
0.00 %				
	Black Dot	White Dot	Mist Line	Foreign Matter
<before></before>	0.50%	3.10%	7.20%	28.80%
<after></after>	0.30%	1.60%	0.90%	1%

Straight pipe connection image



Elbow pipe connection image

				8	
Input Pipe Set	Aset	Bset	Cset	LENSset	
Input Pipe Elbow	1	2	-	-	
Input Pipe Straight	1	-	2	-	
Ferrule Band	2	2	2	1	
Ferrule Seal Ring 2		2	2	1	



Caliber	a: Outer diameter	b: Inner diameter	c: Body outer diameter	d	e	f: Overall length	g: Straight Pipe	h: Elbow Pipe	Weight g
38.0	38.0	35.0	108	5	21	162	140.5	188.5	1,750
48.6	48.6	45.8	114	5	21	162	140.65	203.95	2,090
50.8	50.8	47.8	114	5	21	162	142.25	204.65	2,110
63.5	63.5	60.5	113	5	21	162	142	224.15	2,730

